

PC 50.3 NEW - 66 NEW

E>> BRIGHT EVOLUTION



H.70 Torch H70 H

PC 50.3: H-FIT Torch Connection. PFC - Power Factor Correction (50.1). CNC ready. Automatic Air Pressure control. Easy Manual Air Pressure regulation. Cutting. Grid Cutting. Gouging.

PC 66: H-FIT Torch Connection. CNC ready. Automatic Air Pressure control. Easy Manual Air Pressure regulation. Cutting. Grid Cutting. Gouging.



	PC 50.3	PC 66
	HT70 H FIT	HT70 H FIT
	3ph 400V 50/60Hz	3ph 400V 50/60Hz
Power 60%	7 KVA	11,8 KVA
Max input current	14 A	16,5 A
U _o	240 V	380 V
Range	20 ÷ 45 A	20 ÷ 65 A
Cutting current	45A @ 50% 35A @ 100%	65A @ 60% 50A @ 100%
25cm/min	15 mm	22 mm
Max	20 mm	26 mm
Severance	22 mm	30 mm
Air pressure	16 mm	16 mm
Air capacity	220 l/min @ 5 bar	220 l/min @ 5 bar
Insulation	H	H
Protec. Degree	IP22S	IP22S
Power source's dimensions (LxWxH)	495x195x395 mm	495x195x395 mm
Power Source's Box (LxWxH)	640x260x450 mm	640x260x450 mm
Torch's Box (LxWxH)	500x80x400 mm	500x80x400 mm
Weight box (Power source + torch) /net	20,1 / 19,1 kg	23,3 / 22,3 kg
Code	HPC5031_9983504	HPC5661_9835039